CANOPY CAP® SPECIFICATIONS

CONOPY COP Model CCU

Application: Low profile, economical cap for protecting square or rectangular flues from weather, debris, and animals. All copper hood makes this an ideal choice where owners place a high value on aesthetics. Enclosure of the chimney on two sides of the cap permits selective positioning towards prevailing winds or zones of wind turbulence.


Standard Materials: Hood is copper and all other parts, including screen, are 100% austenitic stainless steel.





E-Z GRIP FASTENER ASSURES A TIGHT FIT ON STANDARD CHIMNEY FLUE SIZES







MODEL # (1" SCREE OPENING*	N (1/2" SCREEN	INSIDE TILE DIAMETER (INCHES)	TILE FLUE DIAMETER (INCHES)	SHIPPING WEIGHT (POUNDS)
CCU-078	CCU-078-S5	7-8 square	8 x 8	- 5
CCU-0812	CCU-0812-S5	8 x 12 rectangular	12 x 12	6
CCU-1212	CCU-1212-S5	11-12 square	12 x 12	7

SIZES: Chimney tile sizes vary greatly from region to region and there are no "standard" flue sizes. Please be sure to accurately measure the inside dimensions of the flue tile before ordering Canopy Cap⁶.

CHIMNEY TYPES: Canopy Cap⁶ is designed for use with square or rectangular flue tiles. 6" x 6" minimum; 13' x 13" maximum.

INSTALLATION: The ICP E-Z Grip Fastener™ assures a secure fit on three standard flue tile sizes. SCREENS: Available as noted above in 1" and 1/2" mesh openings. Check local regulations for what is required in your area.



^{*} Nominal dimension